



identifi&#233;es

Datos t&#233;cnicos Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Conexi&#243;n de CA Potencia asignada (a 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacidad de sobrecarga (a 25 &#176;C hasta m&#225;x. 60 s)2) 4600 W 6300 W 7500 W Salida de corriente nominal de CA (a 230 V, 50 Hz) 16 A 21,7 A 26 A

Technische gegevens Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC-aansluiting Opgegeven vermogen (bij 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overbelastingcapaciteit (bij 25 &#176;C tot max. 60 s)2) 4600 W 6300 W 7500 W Nominale AC-stroom (bij 230 V, 50 Hz) 16 A 21,7 A 26 A

o SBS6.0-10 (Sunny Boy Storage 6.0) from firmware version >= 3.00.00.R 1.2 Target Group This document is intended for qualified persons and end users. Only qualified persons are allowed to perform the activities marked in this document with a warning symbol and the caption

Dati tecnici Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Collegamento CA Potenza massima (a 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacit&#224; di sovraccarico (a 25&#176;C fino a max 60 s)2) 4600 W 6300 W 7500 W Corrente nominale CA uscita (a 230 V, 50 Hz) 16 A 21,7 A 26 A

o SBS5.0-10 (Sunny Boy Storage 5.0) a partire dalla versione del firmware >= 4.00.00.R o SBS6.0-10 (Sunny Boy Storage 6.0) a partire dalla versione del firmware >= 4.00.00.R 1.2 Destinatari Il presente documento &#232; destinato a tecnici specializzati e utenti finali. Le operazioni

Caract&#233;ristiques techniques Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Raccordement AC Puissance assign&#233;e (pour 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacit&#233; de surcharge (&#224; 25 &#176;C jusqu" &#224; 60 sec. max.)2) 4600 W 6300 W 7500 W Courant de sortie nominal AC (pour 230 V, 50 Hz) 16 A 21,7 A3) 26 A Tension nominale AC / Plage de ...

Technical data (preliminary) Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC connection Rated power (at 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overload capacity (at 25&#176;C to max. 60 sec)2) 4600 W 6300 W 7500 W AC nominal current output (at 230 V, 50 Hz) 16 A 21.7 A3) 26 A Nominal AC voltage / AC voltage range 230 V / 172.5 V to 264.5 V

o SBS6.0-10 (Sunny Boy Storage 6.0) from firmware version >= 4.00.00.R 1.2 Target Group This document is intended for qualified persons and end users. Only qualified persons are allowed to perform the activities marked in this document with a warning symbol and the caption

Technische gegevens (onder voorbehoud) Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC-aansluiting Opgegeven vermogen (bij 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overbelastingcapaciteit (bij 25&#176;C tot max. 60 s)2) 4600 W 6300 W 7500 W Nominale AC-stroom (bij

230 V, 50 Hz) 16 A 21,7 A3) 26 A Nominale AC-spanning / AC-spanningsbereik ...

Technical data Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC connection Rated power (at 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overload capability (at 25°C to max. 60 sec.)2) 4600 W 6300 W 7500 W AC nominal current output (at 230 V, 50 Hz) 16 A 21.7 A3) 26 A Nominal AC voltage / AC voltage range 230 V / 172.5 V to 264.5 V

Web: <https://purelysolar.co.za>